

# EASY LIFT® 770

**POWER LIFT MANHOLE COVER WITH WATERTIGHT**

EUROPEAN PATENT GRANTED EU 0741208

AMERICAN PATENT GRANTED US 5937583



**THE ORIGINAL  
POWER LIFT MANHOLE-COVER  
WITH SPRINGS**



Via 2 giugno 21, 20051 Limbiate - MI

Tel. 02 99050241 Fax 02 99050631

[www.fgslamperti.it](http://www.fgslamperti.it)



## ADVANTAGES :

- CLEAR OPENING 770 x 770 mm SQUARE
- DOUBLY GUARANTEED FOR WATERTIGHT
- EFFORTLESS EASY LIFT COVER
- SIMPLE MAINTENANCE
- DIAGONAL CLEAR OPENING 1050 mm



**EASYLIFT 770** is a manhole cover of inspection **planned for the petrol service station.**

**EASYLIFT 770** utilizes a patented system that consents to **lift the cover without any effort**, like all kind of EasyLift cover.

The cover guarantees the **remain itself fixed in any positions** during opening and closing action.

**The opening handle** which is inserted in its own split keep the lock open and **stay there until the cover comes closed in the frame.**

**EASYLIFT 770 is planned to give double watertight** that is guaranted from a special gasket ( tough to the chemical aggression of the fuels ).

At the first, it is given by the geometry of the frame, raised 15 mm from the ground level, so preventing from the rain to penetrate in the tank.

Secondly, in case of persistent rains, flood or however the waterlevel exceeds upper than 15 mm, the watertight is given from the special gasket putted on the frame and pressed from the cover border, when it is closed.

The cover holdes entirely the edge of the frame ( the height from the ground 20 mm only) minimising drastically the dirt's stagnation between the cover and the frame, damaged for the operations of opening - closing and for the correct behavior of the gasket. **The sloping trim consents the passage of the cars without any obstacle.**

**EASYLIFT 770 is provided of 4 holes** at the corner of the frame to fixing the manhole cover with the cement arms by means of shank, plug and/or other like stell tolls.



means of shank,  
plug and/or other  
like stell tolls.



## TECHNICAL SPECIFICATION

**MATERIAL: DUCTILE CAST IRON GS 500/7 ISO 1083**  
**CLEAR OPENING.....770 X 770 mm**  
**TOTAL WEIGHT.....130 Kg**  
**EXTERNAL DIMENSION.....950 X 1067 mm**  
**HEIGHT.....118 mm**

**CLASS C 250 UNI EN 124 NORMS**



Fonderie Ghise Speciali Lamperti Snc  
Tel. 02 99050241 Fax 02 99050631

Via 2 giugno 21 20051 Limbiate MI  
[www.fgslamperti.it](http://www.fgslamperti.it)